

MINI 7 × 40W BEE-EYE

Moving Head Light with LED Ring

350W

RATED POWER



RGBW

4-IN-1 COLOR MIXING

5.5° - 60°

MOTORIZED ZOOM

INDIVIDUAL

LED CONTROL

6.1 kg

NET WEIGHT

COMPACT FIXTURE. VERSATILE EFFECTS.

Seven 40W RGBW bee-eye LEDs combine color wash, strobe, zoom and honeycomb beam effects. Individual LED control and a decorative LED ring offer flexible visual styling for stages, events and entertainment venues.



FRONT VIEW



SIDE VIEW



REAR VIEW

MINI 7 × 40W BEE-EYE

TECHNICAL SPECIFICATIONS

POWER & OPTICS

Input voltage	AC 110-240V, 50/60Hz
Rated power	350W
Main light source	7 × 40W RGBW 4-in-1 bee-eye LEDs
Auxiliary lighting	30 × 0.2W 5050 LEDs (LED strip/ring)
LED lifetime	Approximately 50,000 hours
LED output & control	Full 40W output per main LED; individual LED control
Zoom range	5.5° - 60°, linear adjustment
Color mixing	RGBW; smooth, uniform, flicker-free blending and rainbow effects
Effects & dimming	Color wash, strobe, zoom, honeycomb beam; dimming 0-100%

MOVEMENT & CONTROL

Control modes	DMX512, auto, master/slave, sound-activated
DMX channel modes	42 / 30 / 58 channels
Pan / tilt	540° pan / 270° tilt; 16-bit motorized positioning
Display	1.77-inch color TFT; Chinese/English interface
Monitoring & settings	Device usage time and operating hours; temperature, channel data and software version. Configurable menu and built-in program recall.

CONSTRUCTION & OPERATION

Operating temperature	-20°C to +40°C
Housing	Fire-resistant engineering plastic
Net weight	6.1 kg